



# SWD Quik-Shield® |425 Pour Insulation Foam

**SWD Quik-Shield® |425** is a low viscosity, two component, 2.0 lb. density rigid, closed-cell, polyurethane pour foam, air barrier system. This product is ideal for all types of polyurethane pour foam dispensing equipment.

**SWD Quik-Shield® |425** provides exceptional insulation with an R-Value of 6.8 per inch.

**SWD Quik-Shield® |425** creates a seamless, water resistant barrier that stops air infiltration and removes gaps that allow pests and dust to infiltrate.

**SWD Quik-Shield® |425** is ideal for applications in:

- Insulated masonry wall systems
- Structural insulated panels (SIP)
- Refrigerators
- Refrigerated truck bodies
- Cold storage rooms
- Freezer panels
- Void fill



## **SWD Quik-Shield® |425 an ideal insulation solution**

Closed-cell insulation foam is an ideal way to insulate a wide variety of structures. It provides more insulation in less space and allows for greater design flexibility.

It may be used to fill cavities in concrete, cinder block and masonry walls to increase insulation values. It may also be used with fabricated wall-building systems. It is also an ideal insulator for freezers and refrigeration equipment and structures

**SWD Quik-Shield® |425** is environmentally friendly.

- Reduces energy consumption
- Zero ozone depleting
- Formaldehyde & VOC free
- Improves indoor air quality
- Promotes sustainable design



### **Tested & Approved**

SWD Quik-Shield® |425 meets UL 94 standards and is Energy Star compliant





# SWD Quik-Shield® | 425

## Insulation Foam - Specifications

### CHARACTERISTICS:

#### INSULATION PROPERTIES:

- R-Value – 6.8 per inch
- More insulation in less space
- Saves energy and building material costs
- Performs equally in hot or cold temperatures

#### SEAMLESS INSULATION:

- No joints or seams to leak air or water
- Reduces dust, gas, odor and noise penetration

#### MONOLITHIC:

- Solid, one-piece construction
- Increases structural stability

#### SELF-ADHESIVE:

- No fasteners needed.
- Adheres chemically to wood, metal, masonry, concrete
- Saves material and labor

#### LIGHT WEIGHT:

- High strength to weight ratio.

#### SAFE TO USE:

- Contains no urea formaldehyde.
- Does not give off toxic fumes after application.
- Contains no carcinogens.

#### SHELF LIFE:

- Six months from date of manufacture in unopened containers when stored at 50-80°F.
- Store out of direct sunlight.
- Remove bung covers with caution.

#### MOLD & VOID FILL:

- Free rising to safely completely fill molds, voids and variable space containment and barrier applications.

#### APPROVALS/ COMPLIANCE:

- UL 94 HBF-SWRI File

### PHYSICAL PROPERTIES:

#### RELATIVE INSULATION VALUES (initial values):

k-Factor	R Value/ in.	Thickness
0.147	6.8	1"

#### HANDLING PROPERTIES :

(Based on regular grade formulation @ 75°F)

	"A" Compound	"B" Compound
Viscosity, cps	200	496
Specific Gravity	1.23	1.175
Mixing Ratio	50	50
Mixing Time	10 sec	

#### REACTIVITY PROFILE

Cream Time	22-25 sec
Rise Time	135-145 sec
Tack Free Time	4 min 20 sec

#### FINISHED PRODUCT PROPERTIES

	Procedure*	Values
Core Density, pcf. nominal	D-1622	2.5
Tensile Strength	D-1623	
Compressive Strength psi	D-1621	36
Closed Cell Content	D-2856	95
Water Vapor Transmission	E-96	

**WARNING:** Polyurethane products manufactured or produced from these chemicals may present a serious fire hazard if improperly used or allowed to remain exposed or unprotected. The character and magnitude of any such hazard will depend upon a broad range of factors, which are controlled or influenced by the manufacturing or production process, by the mode of application or installation, and by the function and usage of the particular product. Each person, firm or corporation engaged in the manufacture, production, application, installation, or use of any polyurethane product should carefully determine whether there is a potential fire hazard associated with such product in a specific usage, and utilize all appropriate precautionary and safety measures. This numerical flame spread rating does not reflect hazards presented by this or other material under actual fire conditions.

This information herein is believed to be reliable, however, unknown risks may be present. SWD Urethane Company makes no warranty, expressed or implied, concerning this product's merchantability or fitness for any particular use. The only warranty SWD Urethane Company give is that the product meets the specifications herein listed, and in the event that it does not, that SWD Urethane Company will replace, at its costs SWD Urethane Company's product. The foregoing constitutes SWD Urethane Company's sole obligation with respect to damages, whether direct, incidental or consequential, resulting from the use or performance of the product.