



# SAFETY DATA SHEET

## Quik-Shield 1000

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code:** QS 1000  
**Product Name:** Quik-Shield 1000  
**Company Name:** SWD URETHANE  
539 S. Drew St.  
Mesa, AZ 85210,  
**Web site address:** www.swdurethane.com  
**Emergency Contact:** CHEMTREC  
(800) 424-9300

### 2. HAZARDS IDENTIFICATION

**Flammable Liquids, Category 2**  
**Aspiration Toxicity, Category 1**  
**Skin Corrosion/Irritation, Category 2**  
**Serious Eye Damage/Eye Irritation, Category 2**  
**Acute Toxicity: Inhalation, Category 5**  
**Toxic To Reproduction, Category 2**  
**Aquatic Toxicity (Chronic), Category 2**  
**Specific Target Organ Toxicity (single exposure), Category 3**  
**Specific Target Organ Toxicity (repeated exposure), Category 2**



**GHS Signal Word:** **Danger**

**GHS Hazard Phrases:** H225 - Highly flammable liquid and vapor.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H333 - May be harmful if inhaled.  
H336 - May cause drowsiness or dizziness.  
H361 - Suspected of damaging fertility or the unborn child .  
H373 - May cause damage to through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.

**GHS Precaution Phrases:** P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P235 - Keep cool.

**GHS Response Phrases:** P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P302+352 - IF ON SKIN: Wash with plenty of soap and water.  
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated



# SAFETY DATA SHEET

## Quik-Shield 1000

clothing. Rinse skin with water/shower.  
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+313 - IF exposed or concerned: Get medical attention/advice.  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.  
P314 - Get medical attention/advice if you feel unwell.  
P321 - Specific treatment see information on this label.  
P331 - Do NOT induce vomiting.  
P332+313 - If skin irritation occurs, get medical advice/attention.  
P337+313 - If eye irritation persists, get medical advice/attention.  
P362+364 - Take off contaminated clothing and wash it before reuse.  
P370+378 - In case of fire, use extinguishing media listed in section 5 to extinguish.  
P391 - Collect spillage.  
P403+233 - Store container tightly closed in well-ventilated place.  
P405 - Store locked up.

**GHS Storage and Disposal Phrases:**

**Potential Health Effects (Acute and Chronic):**

The toxicological properties of this material have not been fully investigated.

Use appropriate procedures to prevent opportunities for direct contact with the skin or eyes and to prevent inhalation.

Prolonged or repeated skin contact may cause defatting and dermatitis.

Prolonged or repeated exposure may cause adverse reproductive effects. Chronic exposure may cause visual disturbances. Chronic exposure produces peripheral neuropathy.

**Inhalation:**

Causes respiratory tract irritation. Exposure produces central nervous system depression. Vapors may cause dizziness or suffocation. n-Hexane vapor concentrations can become so high that oxygen is displaced, especially in confined spaces. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. High vapor concentrations may cause drowsiness. May cause hemorrhage of vital organs and coma. May be harmful if inhaled.

**Skin Contact:**

There have been no reports of skin sensitization in people occupationally exposed to n-hexane. Skin sensitization was not observed in a maximization test using 25 volunteers. Prolonged and/or repeated contact may cause irritation and/or dermatitis. Exposure may cause irritation characterized by redness, dryness, and inflammation. May be harmful if absorbed through the skin. Causes skin irritation. May cause irritation with burning pain, itching and redness. Not expected to cause an allergic skin reaction. A single prolonged skin exposure is not likely to result in the material being absorbed in harmful amounts.

**Eye Contact:**

Causes eye irritation. Vapors may cause eye irritation.

**Ingestion:**

May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. Harmful if swallowed. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration hazard if swallowed - can enter lungs and cause damage.



### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
67-64-1	Acetone {2-Propanone}	31.0 %
110-54-3	n-Hexane {Hexyl hydride; Hexane}	27.0 %
64742-49-0	Naphtha (petroleum), hydrotreated light	17.0 %
108-88-3	Toluene {Benzene, Methyl-; Toluol}	14.0 %
110-82-7	Cyclohexane {Benzene, Hexahydro-}	1.0 %

### 4. FIRST AID MEASURES

**Emergency and First Aid**

**Procedures:**

**In Case of Inhalation:** If not breathing, give artificial respiration. Get medical aid immediately. Remove from exposure and move to fresh air immediately. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

**In Case of Skin Contact:** In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

**In Case of Eye Contact:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**In Case of Ingestion:** Potential for aspiration if swallowed. Get medical aid immediately. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Do NOT induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Rinse mouth with water. Consult a physician.

**Signs and Symptoms Of Exposure:** Lung irritation, Chest pain, Pulmonary edema. Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.

**Note to Physician:** Treat symptomatically and supportively. For ingestion, the stomach should be intubated, aspirated, and lavaged with a slurry of activated charcoal--protect the airway from aspiration of gastric contents. Monitor arterial blood gases in cases of severe aspiration. Move out of dangerous area. Consult a physician.

### 5. FIRE FIGHTING MEASURES

**Flash Pt:** -10.00 F Method Used: TAG Closed Cup

**Explosive Limits:** LEL: 1 % UEL: 13 %

**Autoignition Pt:** No data.

**Suitable Extinguishing Media:** Use dry chemical, carbon dioxide, or appropriate foam. Solid streams of water may be ineffective and spread material. Cool containers with flooding quantities of water until well after fire is out.

**Fire Fighting Instructions:** As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. May accumulate static electrical charges, and may cause ignition of its own vapors. Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Wear self contained breathing apparatus for fire fighting if necessary.

**Flammable Properties and Hazards:** No data available.

**Hazards:**



No data available.

## 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case Material Is Released Or Spilled:**

Use proper personal protective equipment as indicated in Section 8.  
Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Remove all sources of ignition. A vapor suppressing foam may be used to reduce vapors. Use only non-sparking tools and equipment. Use a spark-proof tool.  
Personal precautions.  
Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Environmental precautions.  
Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:**

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Take precautionary measures against static discharges. Keep away from heat, sparks and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing dust, mist, or vapor. Do not ingest or inhale. Prevent build up of vapors to explosive concentration. Keep away from sources of ignition - No smoking. Keep container tightly closed.

**Precautions To Be Taken in Storing:**

Keep away from heat and flame. Keep away from sources of ignition. Store in a tightly closed container. Keep from contact with oxidizing materials. Store in a cool, dry, well-ventilated area away from incompatible substances. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
110-54-3	n-Hexane {Hexyl hydride; Hexane}	PEL: 500 ppm	TLV: 50 ppm	No data.
64742-49-0	Naphtha (petroleum), hydrotreated light	No data.	No data.	No data.
108-88-3	Toluene {Benzene, Methyl-; Toluol}	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 50 ppm	No data.
110-82-7	Cyclohexane {Benzene, Hexahydro-}	PEL: 300 ppm	TLV: 100 ppm	No data.

**Respiratory Equipment (Specify Type):**

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

**Eye Protection:**

Wear chemical splash goggles. Face shield and safety glasses.

**Protective Gloves:**

Wear appropriate protective gloves to prevent skin exposure.

**Other Protective Clothing:**

Wear appropriate protective clothing to prevent skin exposure.

**Engineering Controls (Ventilation etc.):**

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne



# SAFETY DATA SHEET

## Quik-Shield 1000

concentrations below the permissible exposure limits.

**Work/Hygienic/Maintenance Practices:** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical States:** [ ] Gas [ X ] Liquid [ ] Solid  
**Appearance and Odor:** solvent odor.  
**Melting Point:** No data.  
**Boiling Point:** 133.00 F - 231.00 F  
**Flash Pt:** -10.00 F Method Used: TAG Closed Cup  
**Evaporation Rate:** No data.  
**Flammability (solid, gas):** No data available.  
**Explosive Limits:** LEL: 1 % UEL: 13 %  
**Vapor Pressure (vs. Air or mm Hg):** No data.  
**Vapor Density (vs. Air = 1):** No data.  
**Specific Gravity (Water = 1):** 0.8  
**Solubility in Water:** No data.  
**Percent Volatile:** No data.  
**Autoignition Pt:** No data.

### 10. STABILITY AND REACTIVITY

**Stability:** Unstable [ ] Stable [ X ]  
**Conditions To Avoid - Instability:** ignition sources, Excessive heat, electrical sparks.  
**Incompatibility - Materials To Avoid:** Oxygen.  
**Hazardous Decomposition or Byproducts:** Carbon monoxide, formed under fire conditions. Carbon oxides.  
**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]  
**Conditions To Avoid - Hazardous Reactions:** Vapors may form explosive mixture with air.



# SAFETY DATA SHEET

## Quik-Shield 1000

### 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** Epidemiology: No information available.  
Teratogenicity: No information available.  
Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies: ACGIH has labeled this substance as a confirmed animal carcinogen.  
Teratogenicity: Teratogenic effects have occurred in experimental animals.  
No information found.  
No data available.

CAS# 67-64-1:

Acute toxicity, LD50, Oral, Rat, 5800. MG/KG.

Results:

Behavioral: Altered sleep time (including change in righting reflex).

Behavioral: Tremor.

- Journal of Toxicology and Environmental Health., Hemisphere Pub., 1025 Vermont Ave., NW, Washington, DC 20005, Vol/p/yr: 15,609, 1985

Acute toxicity, LC50, Inhalation, Rat, 50100. MG/M3, 8 H.

Results:

Kidney, Ureter, Bladder: Changes in bladder weight.

- American Industrial Hygiene Association Journal., AIHA, 475 Wolf Ledges Pkwy., Akron, OH 44311, Vol/p/yr: 20,364, 1959

Acute toxicity, LD50, Skin, Species: Guinea pig, > 9400. UL/KG.

Results:

Behavioral: Somnolence (general depressed activity).

Behavioral: Excitement.

Gastrointestinal:Nausea or vomiting.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 7,559, 1965

**Irritation or Corrosion:** Skin - rabbit - Skin irritation - -24.  
Serious eye damage/eye irritation:  
Eyes - rabbit - Severe eye irritation.

**Carcinogenicity/Other Information:** This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
110-54-3	n-Hexane {Hexyl hydride; Hexane}	n.a.	n.a.	n.a.	n.a.
64742-49-0	Naphtha (petroleum), hydrotreated light	n.a.	n.a.	n.a.	n.a.
108-88-3	Toluene {Benzene, Methyl-; Toluol}	n.a.	3	A4	n.a.
110-82-7	Cyclohexane {Benzene, Hexahydro-}	n.a.	n.a.	n.a.	n.a.

### 12. ECOLOGICAL INFORMATION

**General Ecological Information:** Environmental: Terrestrial: Volatilization and adsorption are expected to be the most important fate processes. Aquatic: Photolysis and hydrolysis in aquatic systems are not expected to be important. Atmospheric: Expected to exist entirely in the vapor phase in ambient air, expected half life 2.8 days. Expected to biodegrade but not bioconcentrate.  
Physical: No information available.  
Terrestrial Fate: Petroleum Ether will have a low to high mobility in soil. Volatilization of petroleum ether is expected as well. Aquatic Fate: Volatilization from water is rapid.



# SAFETY DATA SHEET

## Quik-Shield 1000

Adsorption to sediment will vary. Bioconcentration in aquatic organisms is not expected to be an important fate process because of expected moderate water solubility. Removal may also occur via wet deposition.

Physical: No information found.

Atmospheric Fate: Cyclohexane is expected to partition to the atmosphere where it will rapidly react with hydroxyl radicals. TERRESTRIAL FATE: If released on land, cyclohexane will be lost through volatilization and should leach into the ground.

Cyclohexane is resistant to biodegradation but may biodegrade slowly in the presence of other hydrocarbons that are themselves degraded. AQUATIC FATE: Volatilization from water (estimated half-life 2 hr in a model river) should be the most important fate process occurring in aquatic systems.

Physical: ATMOSPHERIC FATE: In the atmosphere, cyclohexane will degrade by reaction with photochemically produced hydroxyl radicals (half-life 52 hr). The half-life is much faster under photochemical smog conditions with half-lives as low as 6 hr being reported.

CAS# 67-64-1:

LC50, Rainbow Trout (*Oncorhynchus mykiss*), fingerling, 6100000. UG/L, 24 H, Mortality, Water temperature: 10.00 C C, pH: 8.00; Acute Lethality, and Sub-lethal Effects of Acetone, Ethanol, and Propylene Glycol on the Cardiovascular and Respiratory Systems of Rainbow Trout, Majewski, H.S., J.F. Klaverkamp, and D.P. Scott, 1978

LC50, Water Flea (*Daphnia magna*), 23500000. UG/L, 48 H, Mortality; Methodology for Assessing the Acute Toxicity of Chemicals Sorbed to Sediments: Testing the Equilibrium Partitioning Theory, Ziegenfuss, P.S., W.J. Renaudette, and W.J. Adams, 1986

**Bioaccumulative Potential:** Bioaccumulation: *Leuciscus idus* (Golden orfe) - 3 d.  
Bioconcentration factor (BCF): 94

**Mobility in Soil:** No data available.

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Observe all federal, state, and local environmental regulations.

### 14. TRANSPORT INFORMATION

**GHS Classification:** Flammable Liquids, Category 2 - Danger! Highly flammable liquid and vapor  
Aspiration Toxicity, Category 1 - Danger! May be fatal if swallowed and enters airways.  
Skin Corrosion/Irritation, Category 2 - Warning! Causes skin irritation  
Serious Eye Damage/Eye Irritation, Category 2 - Warning! Causes serious eye irritation  
Acute Toxicity: Inhalation, Category 5 - Warning! May be harmful if inhaled  
Toxic To Reproduction, Category 2 - Warning! Suspected of damaging fertility or the unborn child  
Aquatic Toxicity (Chronic), Category 2 - Toxic to aquatic life with long lasting effects  
Specific Target Organ Toxicity (single exposure), Category 3 - Warning! May cause respiratory irritation, or may cause drowsiness and dizziness  
Specific Target Organ Toxicity (repeated exposure), Category 2 - Warning! May cause damage to {<target organs>} through prolonged or repeated exposure



# SAFETY DATA SHEET

## Quik-Shield 1000

### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Adhesives, [containing a flammable liquid]  
**DOT Hazard Class:** 3 FLAMMABLE LIQUID  
**UN/NA Number:** UN1133 **Packing Group:** II



### LAND TRANSPORT (Canadian TDG):

**TDG Shipping Name:** Adhesives, [containing a flammable liquid]  
**UN Number:** 1133 **Packing Group:** II  
**Hazard Class:** 3 - FLAMMABLE LIQUID **TDG Classification:**

### MARINE TRANSPORT (IMDG/IMO):

**IMDG/IMO Shipping Name:** Adhesives, [containing a flammable liquid]  
**UN Number:** 1133 **Packing Group:** II  
**Hazard Class:** 3 - FLAMMABLE LIQUID  
**IMDG EMS Page:** **IMDG MFAG Number:**  
**Marine Pollutant:** Yes

### AIR TRANSPORT (ICAO/IATA):

**ICAO/IATA Shipping Name:** Adhesives, [containing a flammable liquid]

## 15. REGULATORY INFORMATION

#### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
110-54-3	n-Hexane {Hexyl hydride; Hexane}	No	Yes 5000 LB	Yes
64742-49-0	Naphtha (petroleum), hydrotreated light	No	No	No
108-88-3	Toluene {Benzene, Methyl-; Toluol}	No	Yes 1000 LB	Yes
110-82-7	Cyclohexane {Benzene, Hexahydro-}	No	Yes 1000 LB	Yes

#### CAS # Hazardous Components (Chemical Name)

#### Other US EPA or State Lists

67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: No; NJ EHS: Yes - 0006; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: No; WI Air: Yes
110-54-3	n-Hexane {Hexyl hydride; Hexane}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1340; NY Part 597: Yes; PA HSL: Yes - 1; SC TAP: Yes; WI Air: Yes
64742-49-0	Naphtha (petroleum), hydrotreated light	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
108-88-3	Toluene {Benzene, Methyl-; Toluol}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 1866; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
110-82-7	Cyclohexane {Benzene, Hexahydro-}	CAA HAP,ODC: No; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test, 8D TERM; CA PROP.65: No; CA TAC, Title





# SAFETY DATA SHEET

## Quik-Shield 1000

Page: 9 of 10  
Printed: 05/18/2015  
Revision: 05/18/2015  
Supersedes Revision: 04/06/2015

8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5;  
NC TAP: No; NJ EHS: Yes - 0565; NY Part 597: Yes; PA  
HSL: Yes - E; SC TAP: No; WI Air: No

CAS #	Hazardous Components (Chemical Name)
67-64-1	Acetone {2-Propanone}
110-54-3	n-Hexane {Hexyl hydride; Hexane}
64742-49-0	Naphtha (petroleum), hydrotreated light
108-88-3	Toluene {Benzene, Methyl-; Toluol}
110-82-7	Cyclohexane {Benzene, Hexahydro-}

### International Regulatory Lists

Canadian DSL: Yes; Canadian NDSL: No  
Canadian DSL: Yes; Canadian NDSL: No  
Canadian DSL: Yes; Canadian NDSL: No  
Canadian DSL: Yes; Canadian NDSL: No  
Canadian DSL: Yes; Canadian NDSL: No

**Regulatory Information:** This product contains chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372.

CAS# 110-54-3, n-Hexane: 27.0%  
CAS# 108-88-3, Toluene: 14.0%  
CAS# 110-82-7, Cyclohexane: 1.0%

## 16. OTHER INFORMATION

**Revision Date:** 05/18/2015

**Hazard Rating System:**

HEALTH		2
FLAMMABILITY		3
PHYSICAL		0
PPE		K

**HMIS:**

**Additional Information About This Product:** No data available.

**Company Policy or Disclaimer:**

While the information and recommendations in this publication are given to the best of our knowledge, and information at the date of publication, nothing herein is to be construed as a warranty, expressed or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information, and recommendations or the suitability of any product for its own particular purpose.

The product may present hazards and should be used with caution. While certain hazards are described in this Safety Data Sheet, no guarantee is made that these are the only hazards that exist. Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED SWD EMPLOYEE SHALL PROVIDE, OR MAKE AVAILABLE, DATA SHEETS FOR SWD PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT THE WRITTEN PERMISSION OF SWD. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET OR QUESTIONS REGARDING THIS DATA SHEET SHOULD BE DIRECTED TO SWD AT 800-828-1394.