



QUIK-SHIELD 106

Open-Cell Spray Foam Insulation

Quik-Shield 106 is an applicator-friendly open-cell foam that is easy to use, provides exceptional yield, and has high quality that you can depend on. It is ideal for applicators who are looking for a foam that delivers consistent results under almost any condition. In addition, Quik-Shield 106 has 1-hour reentry and doesn't require an ignition barrier in unvented attics, saving you time and money.



EASY TO USE

Drop-In Product • Wide Range of Temperatures and Jobsite Conditions

Quik-Shield 106 is easy to use, helping sprayers work faster, better, and in more climate conditions. This open-cell product will spray quality foam without having to continually adjust equipment settings. Additionally, QS106 is simple to dial in, applicators who are familiar with other open-cell foam can also get great results from Quik-Shield 106.



GREAT YIELD

Up to 20,000 Bd. Ft. • Lower Material Cost

Lower density corresponds to higher yields, and Quik-Shield 106's Low Density of 0.4 pounds per cubic foot (pcf) enables it to provide high yields. At up to 20,000 board feet per set, QS106 delivers a low board foot cost, which reduces your material costs and enables you to be more competitive in your bids.



QUALITY

Consistent Application • No Voids or Adhesion Issues • No Odor

Quik-Shield 106 sprays consistently for a good install done right the first time, every time, with no voids or adhesion issues. In addition, Quik-Shield 106 has low VOCs and is virtually odor-free, unlike some other foams.



1-HOUR REENTRY

No Fans Required • Stay in Compliance • Keep Other Trades on Schedule

Quik-Shield 106 was engineered better than competitors' products, which is why we have the industry's leading reentry time of only 1 hour without the use of fans for new residential construction. No need to shut down a job site for 24 hours, and everyone stays in compliance with the manufacturer's instructions.